



2009 SPARTAN

Metro Star/Fort Garry Fire Apparatus



SPECIFICATIONS

2009 SPARTAN

Metro Star Fort Garry Fire Apparatus

KEY FEATURES / KEY SPECS

CAB

- 5 Passenger, 4 SCBA Seats
- GVWR 42,000 Lb.

BODY

- Fort Garry

ENGINE

- ISC Cummins 360 HP, 1050 Torque
- 5 Speed

TRANSMISSION

- Allison 3500 EVS

PUMP

- Darley 5000 LPM
- Pump and Roll
- Driver Side Pump Panel
- Rear Pump Panel

WATER TANK

- Pro-Ploy 1210 US Gallon

TANK

- 30 Gallon Class A
- 100 Gallon Class B

FOAM PUMP

- Foam Pro 2002
- Class A & B

FRONT SUSPENSION

- 18,000 Taper Leaf Springs
- 385/65R22.5

REAR SUSPENSION

- 24,000 Neway Air
- 11R22.5

ADDITIONAL SPECIFICATIONS

- Meets NFPA 1901
- FRC Governor Pressure/RPM

- FRC Tank Level
- Access Quic-Lift Ladder, 24' Ladder, 12' Roof Ladder, 10' Attic Ladder
- Onspot Auto Tire Chains
- TFT Ball Intake
- 1 - Rear 4" intakes
- 1 - Rear 5" intakes
- Elkhart Vulcan RF Monitor
- 2 - 44 mm Crosslay / Foam
- 65 mm Crosslay / Foam
- 65 mm Crosslay
- 2 - 100 mm Side Discharge
- 3 - 65mm Discharge
- 2 - 100mm 10' Hard Suction Line
- Honda EM3800 SX Generator

