



## 2018 MAXI URBAN INTERFACE 4X4





## MAXI URBAN INTERFACE SPECIFICATIONS

### CHASSIS

- 4x4, 2019 Freightliner M2-106
- Maxi Pump & Roll

### ENGINE

- Cummins L9 350 Hp

### TRANSMISSION

- Allison Transmission 3000 Evs
- 5-Speed, with "Package 265"

### PUMP

- Narrow Pumphouse Design
- Hale Rsd125 Pump Nfpa Rated at 1250 Gpm

### WATER TANK

- Brayneck-Canaplast

### TANK

- 1200 GAL (US) Booster Tank and a 30 GAL (US) Foam Tank

### FOAM PUMP

- A Foampro 2001 12 Volt.
- Class A Foam

### FRONT SUSPENSION

- The Taper Leaf Front Suspension Spring Capacity Shall be Rated at 16,000Lb.


### REAR SUSPENSION

- The Rear Leaf Spring Suspension Capacity Rated at 30,000Lb.

### SPECIFICATIONS:

- Meets NFPA 1901 - 2016 Standard
- Top Speed 112 Km/H (70 Mph) +/- 3 Km/H
- Differential Ratio Around 5.86
- 3 Rear Seats Non Suspension with SCBA Brackets
- Booster Reel with 200 Ft of 1" Hose
- Deck Gun #TFT Y2-E84A with in cab joystick

- Nozzle #B-Tos-Erp (120 Gpm)
- 4 Compartments for Scba Cylinders
- Doors are Amdor Brand
- Equipped with a Zico One Hydraulic Ladder Rack
- 2 Frc Model Spa 900-Q70 Led Scene Lights
- Detachable Winch Warn 9.5 Cti



SALES / SERVICE / INSPECTIONS  
866 962 1218 WESTVAC.COM